

P R O F E S S I O N A L L I N E



RX Hepa
380e - 450e - 500e





RX Hepa CLASS A **380e - 450e - 500e**

Heavy duty two motor upright vacuum for large areas

STRENGTHS

- › Design, technology and construction 100% made in Italy
- › The machine that won the White House
- › Strong and reliable – ideal for contract cleaners
- › Telescopic handle for maximum comfort
- › Ultra strong with metal brush supports with ball-bearings
- › Complete set of accessories on board
- › Quick release double support suction body/base housing
- › Stainless steel base guides
- › Available in 3 sizes: 380 (15"), 450 (18"), 500 (20")
- › High efficiency electric motors (Class A)



RX Hepa

Quality and reliability world wide recognized!



MAINTENANCE WITHOUT TOOLS

The 5000 RPM dynamically balanced roller and metal supports with ball bearings can be quickly replaced without tools.
The RX is equipped with 4 rubber wheels as well as two side cylinders to glide flush with the wall.

STAINLESS STEEL BASE GUIDE

Two wear resistant stainless steel base guides provide a shockproof system.
Two position operation provides easy transition over thresholds or to lay down horizontally to go under beds and furniture.

ACCESSORIES ON BOARD

The accessories on board are: stretch hose with swivel cuffs, handle with suction control (on request), telescopic wand, crevice tool, upholstery tool, easy to access on the upper part of the suction body.

ELECTRONIC PROTECTION

Electronic control provides for a soft start, overload indication for the correct height adjustment and motor shut off to protect the drive timing belt and all moving parts.


ENGINEERED TO LAST

The electric motors are manufactured by the sister company Rotafil Padova- Italy and use the bar type commutator, the world's best technology for safety and reliability.
The high efficiency of the motors provides low power consumption and high performance (Class A). Precision engineered and computer balanced motors assure low sound level and long service life. The electronic controls protect motors from overload assuring the machine is working at peak performance.



RX is equipped with 6 stages of filtration. At the final stage an electrostatic microfilter (3M Filtrete) ensures more than 98% of filtration efficiency at 0.3 micron. You can install the optional filters S-Class Hepa for healthcare environments, which assures 99.97% of filtration efficiency at 0.3 micron. To trap offensive odors use the Lindhaus Carbon Active/Microfilters. All exhaust filters are impregnated with Total antiseptic treatment to avoid the outflow of living micro-organisms.

NET EFFICIENCY FILTRATION





APPLICATIONS

RX is available in three sizes and can operate on any size carpeted surface: hotel rooms, corridors, ballroom, show rooms, stores, restaurants, cinemas, conference rooms, cruise ships etc.



MOTOR PROTECTION FILTER

All suction air and dust are super filtered and particular attention has been placed on the power nozzle, equipped with a washable motor protection filter easily replaceable without and tools.

SPECIAL FILTERS

RX can be equipped with many special filters (optional) for use in healthcare environments, research laboratories etc: 3 layer Micropore bag, motor protection filter, Carbon Active/ Microfilter and at the exhaust an S-Class Hepa filter.

The company Lindhaus srl reserves its right to make any modifications without any prior notice.

TECHNICAL SPECIFICATIONS	RX HEPA 380e	450e	500e
Input power (W)	930	950	950
Water lift mm/H ₂ O (in/ H ₂ O)	2300 (90)	2300 (90)	2300 (90)
Air volume lt/sec (cfm)	49 (103.8)	49 (103.8)	49 (103.8)
Motor protection	termo/amp.	termo/amp.	termo/amp.
Two ply paper bag (lt.)	4	4	4
Washable tnt bag and micropore	optional	optional	optional
Exhaust microfilter 3m filtrate	standard	standard	standard
"S" class hepa filter	optional	optional	optional
Cogged drive belt	standard	standard	standard
Electronic overload/speed control	standard	standard	standard
Center convergent bristles brush (rpm)	5000	4500	4500
Anti wear shoe plate	stainless steel	stainless steel	stainless steel
Working capacity m ² /h (sq.Ft/h)	630 (6700)	750 (8000)	850 (9100)
Noise level db (A)	68,6	68,6	68,6
Total weight kg (lb)	7,79 (17.2)	8,16 (17.9)	8,25 (18.2)
Cord length mt. (Ft.)	10 (41)	10 (41)	10 (41)

APPROVALS:



HEADQUARTERS › LINDHAUS SRL

Via Belgio, 22 Z.I. 35127 › Padova, ITALY
tel. +39 0498700307 › fax +39 049 8700605
vacuum@lindhaus.it › www.lindhaus.it

LINDHAUS USA

Minneapolis › Minnesota USA
info@lindhaus.com › www.lindhaus.com

DISTRIBUTOR / DEALER